



ANTENNA EXPERTS

E-mail: info@antennaexperts.in Website: www.antennaexperts.in

Model # BVM-118-400 118 – 400 MHz. 2.5 dBi Gain

VHF UHF Ground-To-Air Vehicular Mount Omni-Directional Antenna

DESIGN FEATURES: BVM-118-400 Omni-directional VHF UHF ground to air aviation band antenna is rugged all weather model, enclosed in a ABS radome, uses high class brass and aluminum alloy and does not require any field tuning or adjustments. The compact size of omni-directional VHF UHF ground to air antenna allows easy handling, shipping and highly suitable receiving, transmitting, scanning, monitoring, surveillance and jamming applications without having the requirement of multiple antennas. The N-Female termination of antenna is fixed at the bottom of the mounting flange for complete weather protection. Cylindrical shell/enclosure is used for low wind loading and for minimal effect of ice formation on the antenna operation as well as providing an aesthetically pleasing appearance.

CONSTRUCTIONS: The VHF UHF ground to air aviation band antenna is consisting of large diameter radiating elements stacked vertically and enclosed in ABS radome. The special “Choke and Spark Gap” technique is used for smooth VSWR and constant 3dBi. gain over the entire 118-400 MHz. frequency band. The UV resistant ABS enclosure has excellent transparency for RF signals and enough strength to withstand specified wind loads.

MOUNTING OPTIONS: This VHF UHF ground to air aviation band antenna can be supplied with standard NATO 4 holes pattern with or without stainless steel spring base. The mounting hardware is made of marine grade stainless steel. Customized mounting arrangements can also be supplied on request.



ELECTRICAL SPECIFICATIONS:

Frequency Range	118-400 MHz.
Gain	2.5 dBi.
Bandwidth	Entire Band
Polarization	Vertical
Input Impedance	50 Ohms
Radiation Pattern	Omni-directional
Vertical Beam-width –Half Power Points.	78 Degrees
VSWR – Better Than	2.5:1
RF Power Handling Capacity	500 Watts.
Input Termination	N-Female

MECHANICAL SPECIFICATIONS:

Materials	6063T6 Aluminum & ABS
Mounting Hardware -Materials	Marine Grade Stainless Steel
Wind Rating	200 Km/Hr.
Overall Length	1.1 Meter
Shipping Length	1.15 Meter
Mounting Type	NATO 4 Holes or Customized
Enclosure Materials	UV Resistant ABS
Enclosure Length	900 mm
Gross Weight	5 Kgs.

ENVIRONMENTAL SPECIFICATIONS:

Operating Temperature	(-)30 to +70 Degrees Celsius
Storage Temperature	(-)40 to +80 Degrees Celsius
Humidity	0 to 95% RH

Please contact us for further information like radiation patterns, VSWR & drawing etc.

Note: All information contained in the datasheet is subject to change without any prior notice.