

Fiber Glass Omnidirectional High Gain Collinear Antenna

AC10-2450

2300-2600 MHz.

10 dBi. Gain

DESIGN FEATURES: AC10-2450 UHF Fiberglass Omni-directional Collinear Antenna is rugged all weather model uses high class brass and aluminum alloy and does not require any field tuning or adjustments. All junctions are fully welded to prevent RF inter-modulation and antenna is completely protected within a high-tech ruggedized radome to ensure survivability in the worst environments. The heavy duty fiberglass enclosure has excellent transparency for RF signals and enough strength to withstand specified wind loads. The compact size of fiber glass collinear antenna allows easy handling and shipping. The antenna is supplied with olive green military color. Other customized color can also be supplied on request.

CONSTRUCTIONS: The AC10-2450 is a center fed design which eliminates the distortion of the radiation pattern and ensures a true omni-directional horizontal pattern. The special stub matching is used for smooth VSWR and constant gain over the specified frequency band. The UHF collinear antenna consist of large diameter brass radiating elements stacked vertically, fed in phase and enclosed in fiber glass tube. The antenna termination is enclosed at bottom of the antenna for complete weather protection. The stainless steel mounting hardware is supplied with the antenna.



ELECTRICAL SPECIFICATIONS:

Frequency Range	2300 - 2600 MHz.
Gain	10 dBi.
Bandwidth	200 MHz.
Polarization	Vertical
Input Impedance	50 Ohms.
Radiation Pattern	Omni Directional
Vertical Beam-width –Half Power Points	6 Degrees
VSWR	1:1.5
RF Power Handling Capacity	200 Watts.
Input Termination	N-Female

MECHANICAL SPECIFICATIONS:

Mounting Hardware	Stainless Steel
Gross Weight	4 Kgs.
Wind Rating	200 Km/Hr.
Overall Length	1.7 Meters
Shipping Length	1.8 Meters
Support Pipe Outer Diameter	51 mm
Support Pipe Materials	Aluminum
Maximum Mount Pipe Diameter	51 mm (2 Inches)
Enclosure Materials	Fiberglass
Enclosure Outer Diameter	45 mm
Enclosure Length	1350 mm

ENVIRONMENTAL SPECIFICATIONS:

Operating Temperature	(-) 30 to +70 Degrees Celsius
Storage Temperature	(-) 40 to +80 Degrees Celsius
Humidity	0 to 95% RH

Please contact us for further information like Azimuth & Elevation radiation patterns & frequency Vs VSWR of the antenna.

Note: All information contained in the datasheet is subject to change without any prior notice.