



ANTENNA EXPERTS

E-mail: info@antennaexperts.in Website: www.antennaexperts.in

Model AH-5500


5100 – 5900 MHz.

16 dBic. Gain

CIRCULAR POLARIZED LHCP or RHCP HELICAL ANTENNA

DESIGN FEATURES: The AH-5500 uses extended stubs to provide the greater gain while maintaining the wider beam-width. This high-gain low-profile antennas use Circular Polarization Antenna Technology - which delivers better penetration through obstruction and interference. This commercial grade antenna provides superior performance as compare to significantly larger and more expensive products. Our AH series helical antennas are smaller than conventional yagi antenna. The AH-5500 Helical Antenna is supplied with a specially designed mounting

arrangement for steering the antenna in both planes, over 360 Degrees in Azimuth and 90 Degrees in Elevation for terrestrial and satellite links.



CONSTRUCTIONS: The AH-5500, like all our AH series helical antennas, utilizes circular polarization to minimize the effects of multipath interference. Both Right Hand Circular Polarized (RHCP) and Left Hand Circular Polarized (LHCP) helical antenna models are available. The AH-5500 Helical Antenna is light weight, broadband and rugged helical antennas, supplied with ABS radome to protect the antenna from environment. Cylindrical enclosure is used for low wind loading and for minimal effect of ice formation on the helical antenna operation as well as providing an aesthetically pleasing appearance.

ELECTRICAL SPECIFICATIONS:

Frequency Range	5100 - 5900 MHz.
Gain - Typical	16 dBic.
Bandwidth	Entire Band
Polarization	Circular LHCP or RHCP
Input Impedance	50 Ohms.
Radiation Pattern	Directional
Horizontal Beam-width –Half Power Points	35 +/-5 Degrees Typical
Front to Back Ratio	17+/-1 dB. Typical
VSWR – Better Than	1.5 : 1
RF Power Handling Capacity	200 Watts.
Input Termination	N-Female

MECHANICAL SPECIFICATIONS:

Mounting Hardware	Marine Grade Stainless Steel
Gross Weight – Less Than	1 Kg.
Wind Rating	200 Km/Hr.
Overall Length	300 mm
Shipping Length	350 mm
Radiating Materials	High Quality Copper
Enclosure diameter	45 mm
Enclosure Materials	High Strength ABS
Enclosure diameters	45 mm
Maximum Mount Pipe Diameter	52 mm (2 Inches)
Elevation Tilt Mechanism	0-90 Degrees

ENVIRONMENTAL SPECIFICATIONS:

Operating Temperature	(-) 30 to +70 Degrees Celsius
Storage Temperature	(-) 40 to +80 Degrees Celsius
Humidity	0 to 95% RH

Note: All information contained in the datasheet is subject to change without any prior notice. Customized mounting & color can also be supplied on request. [Please contact us for Radiation Patterns and Frequency Vs VSWR Graph](#)