



ANTENNA EXPERTS

E-mail: info@antennaexperts.in Website: www.antennaexperts.in

Model JC-134-174 134 – 174 MHz. 0 dBi. Gain


Omni-directional Jammer Collinear Antenna

DESIGN FEATURES: The JC-134-174 Jammer Collinear Antenna is rugged all weather model, enclosed in a Fiber Glass enclosure, uses high class aluminum alloy and does not require any field tuning or adjustments. The N-Female termination of antenna is fixed at the bottom of NATO mounting base antenna to provide complete weather protection. This fiber glass jammer collinear antenna is specially designed to mount on the side of the vehicle with the help antenna adaptor base plate. The antenna uses standard NATO 4 holes pattern base which is suitable to mount the antenna directly on the antenna adaptor base plate. Similarly the antenna can also be supplied with pole mounting hardware (optional). Other customized mounting can also be supplied on request.



CONSTRUCTIONS: The special co-axial stub and spark gap techniques are used for smooth VSWR and gain over entire the 134 - 174 MHz frequency band. The jammer collinear antenna consists of large diameter brass radiating elements stacked vertically, fed in phase and enclosed in fiber glass housing. The Fiber Glass has excellent transparency for Radio Signal and mechanically Robust to support extra mechanical strength to the collinear antenna. Cylindrical enclosure is used for low wind loading and for minimal effect of ice formation on the antenna operation as well as providing an aesthetically pleasing appearance. The antenna supplied with olive green colour for defense application.

ELECTRICAL SPECIFICATIONS:	
Frequency Range	134 - 174 MHz.
Gain at Center Frequency	0 dBi.
Bandwidth	40 MHz.
Polarization	Vertical
Input Impedance	50 Ohms
Radiation Pattern	Omni-directional
Vertical Beam-width –Half Power Points	78 Degrees
VSWR - Better Than	2.5:1
RF Power Handling Capacity	150 Watts
Input Termination	N-Female
MECHANICAL SPECIFICATIONS:	
Wind Rating	170 Km/Hr.
Overall Length	900 mm
Shipping Length	1000 mm
Support Pipe Materials	6063T6 Aluminum Alloy
Support Pipe Diameter	50 mm
Mounting Type	NATO Interface or Customized
Enclosure Materials	Fiberglass
Enclosure Outer Diameters	44 mm
Radiating Elements - Materials	All Brass
Gross Weight	1.8 Kgs.
ENVIRONMENTAL SPECIFICATIONS:	
Operating Temperature	(-) 30 to +70 Degrees Celsius
Storage Temperature	(-) 40 to +80 Degrees Celsius
Humidity	0 to 95 % RH



Please contact us for further information like drawing, radiation patterns & VSWR graph etc.
Note: All information contained in the datasheet is subject to change without any prior notice.