



ANTENNA EXPERTS

E-mail: info@antennaexperts.in Website: www.antennaexperts.in

Model JC12-2130

2110 – 2170 MHz.

12 dBi. Gain

HIGH GAIN JAMMER COLLINEAR ANTENNA

DESIGN FEATURES: The JC12-2130 Jammer Collinear Antenna is rugged all weather model, enclosed in a Fiber Glass enclosure, uses high class aluminum alloy and does not require any field tuning or adjustments. This fiber glass jammer collinear antenna is specially designed to mount on the roof-top hole of the vehicle or can be supplied to mount the antenna directly on the jammer equipments. The JC12-2130 antenna is highly suitable for man-pack and vehicle mounting applications. Similarly the antenna can also be supplied with pole mounting hardware (optional).

CONSTRUCTIONS: The special co-axial stub and spark gap techniques are used for smooth VSWR and constant 12dBi. gain over entire the 2100 - 2170 MHz frequency band. The JC12-2130 jammer collinear antenna consists of large diameter brass radiating elements stacked vertically, fed in phase and enclosed in fiber glass housing. The Fiber Glass has excellent transparency for Radio Signal and mechanically Robust to support extra mechanical strength to the collinear antenna. The antenna can also be supplied with olive green colour for defense application.



ELECTRICAL SPECIFICATIONS:	
Frequency Range	2110 - 2170 MHz.
Gain	12 dBi.
Bandwidth	Entire Band
Polarization	Vertical
Input Impedance	50 Ohms
Radiation Pattern	Omni-Directional
Vertical Beam-width –half Power Points	8 Degrees
VSWR	1:1.5
RF Power Handling Capacity	150 Watts
Input Termination	N-Female

MECHANICAL SPECIFICATIONS:	
Mounting Hardware	Stainless Steel
Weight Approx	2 Kgs.
Overall Length	2 Meters
Shipping Length	2.1 Meters
Support Pipe O.D.	38 mm
Support Pipe Materials	Aluminum
Radiating Materials	All Brass
Maximum Mount Pipe Diameter	52 mm (2 Inches)
Enclosure Materials	Fiber Glass
Enclosure Outer Diameters	32 mm

ENVIRONMENTAL SPECIFICATIONS:	
Operating Temperature	(-) 30 to +70 Degrees Celsius
Storage Temperature	(-) 40 to +80 Degrees Celsius
Humidity	0 to 95% RH