



ANTENNA EXPERTS

E-mail: info@antennaexperts.in Website: www.antennaexperts.in

Model # JCM6-1820 1800 – 2000 MHz. 6 dBi. Gain

High Gain Manpack Jammer Collinear Antenna for GSM & CDMA

DESIGN FEATURES: The JCM6-1820 Jammer manpack collinear antenna is rugged all weather model, enclosed in a ABS radome, uses high quality brass radiating elements and does not require any field tuning or adjustments. The compact size of omni-directional antenna allows easy handling, shipping and highly suitable for transmitting, receiving GSM/CDMS bands without having the requirement of multiple antennas. Cylindrical enclosure is used for low wind loading and for minimal effect of ice formation on the antenna operation as well as providing an aesthetically pleasing appearance.

CONSTRUCTIONS: The jammer collinear antenna is supplied complete in assembled condition. This high gain jammer manpack antenna has smooth VSWR and constant Gain over the 1800-2000 MHz GSM/CDMA frequency bands. The JCM6-1820 jammer antenna consists of ultra corrosion resistant radiating elements and enclosed in ABS housing. The ABS has excellent transparency for Radio Signals and mechanically Robust to support extra mechanical strength to the antenna.

MOUNTING: The high gain man pack jammer collinear antenna is designed & supplied Man-pack application. The high gain man pack jammer antenna uses N-Male termination at the base so that same can be mounted directly on the equipment/transmitter. Optional: The antenna can be supplied with spring base if required.

NOTE: Part # JCM6-1820-S with spring fitted at base. Add 100mm in overall length and add 250 Grams in gross weight.

ELECTRICAL SPECIFICATIONS:

Frequency Range	1800 - 2000 MHz.
Gain - Typical	6 dBi.
Bandwidth	Entire Band
Polarization	Vertical
Input Impedance	50 Ohms.
Radiation Pattern	Omni-directional
-3dB. Vertical Beam-width	40 Degrees
VSWR – Better Than	2:1
RF Power Handling Capacity	50 Watts.
Input Termination	N-Male

MECHANICAL SPECIFICATIONS:

Wind Rating	60 Km/Hr.
Mounting Type	Directly on Transmitter
Overall Length	400 mm
Shipping Length	500 mm
Support Pipe Materials	6063T6 Aluminum Alloy
Enclosure/Radome Diameter	32 mm
Enclosure Materials	ABS
Radiators & Support Pipe	6063T6 Aluminum Alloy
Gross Weight	400 Grams
Finish / Color	Olive Green

ENVIRONMENTAL SPECIFICATIONS:

Operating Temperature	(-) 30 to +70 Degrees Celsius
Storage Temperature	(-) 40 to +80 Degrees Celsius
Humidity	0 to 95 % RH



Note: All information contained in the datasheet is subject to change without any prior notice.