



# ANTENNA EXPERTS

E-mail: [info@antennaexperts.in](mailto:info@antennaexperts.in) Website: [www.antennaexperts.in](http://www.antennaexperts.in)

Model # JD-1018

1000 – 1800 MHz.

2.5 dBi. Gain

## OMNI-DIRECTIONAL JAMMER DISCONE ANTENNA

**DESIGN FEATURES:** The JD-1018 Jammer Discone Antenna is rugged all weather model, enclosed in a ABS radome, uses all ultra corrosion resistant aluminum alloy and does not require any field tuning or adjustments. The compact size of omni-directional antenna allows easy handling, shipping and highly suitable for transmitting, receiving without having the requirement of multiple antennas. Cylindrical enclosure is used for low wind loading and for minimal effect of ice formation on the antenna operation as well as providing an aesthetically pleasing appearance.

**CONSTRUCTIONS:** The jammer discone antenna is supplied complete in assembled condition. This discone antenna has smooth VSWR and constant Gain over the 1000 - 1800 MHz frequency band. The JD-1018 jammer discone antenna consists of ultra corrosion resistant radiating elements and enclosed in ABS housing. The ABS has excellent transparency for Radio Signal and mechanically Robust to support extra mechanical strength to the discone antenna.

**MOUNTING:** Following three options are available to choose from:

(1) Roof-top hole mounting on the vehicle which requires a 16mm hole through roof of the vehicle with N-Female termination. (2) Man-pack mounting; in this you can mount the antenna directly on the equipment with M-male termination. (3) Antenna can be supplied with pole mounting hardware; in this the mounting hardware is suitable for mounting on any outer diameter pipe between 32-51mm.



### ELECTRICAL SPECIFICATIONS:

Frequency Range	1000 - 1800 MHz.
Gain	2.5 dBi.
Bandwidth	Entire Band
Polarization	Vertical
Input Impedance	50 Ohms.
Radiation Pattern	Omni-directional
Vertical Beam-width -Half Power Points	78 Degrees
VSWR – Better Than	2:1
RF Power Handling Capacity	500 Watts.
Input Termination	N-Female

### MECHANICAL SPECIFICATIONS:

Wind Rating	200 Km/Hr.
Mounting Type	Roof Hole, manpack or side Pole
Overall Length	180 mm
Shipping Length	200 mm
Support Pipe Materials	Aluminum
Insulator Materials	Teflon & Nylon
Enclosure Materials	ABS
Radiating Elements & Support Pipe - Materials	6063T6 Aluminum Alloy
Gross Weight	1 Kg.

### ENVIRONMENTAL SPECIFICATIONS:

Operating Temperature	(-) 30 to +70 Degrees Celsius
Storage Temperature	(-) 40 to +80 Degrees Celsius
Humidity	0 to 95 % RH

Note: All information contained in the datasheet is subject to change without any prior notice.