



ANTENNA EXPERTS

E-mail: info@antennaexperts.in Website: www.antennaexperts.in

Model # MC6-160

156 – 162MHz

6 dBi. Gain

MARINE BAND OMNI-DIRECTIONAL COLLINEAR ANTENNA

DESIGN FEATURES: MC6-160 marine band fiberglass omni-directional collinear antenna is rugged all weather model uses high class brass and aluminum alloy and does not require any field tuning or adjustments. All junctions are fully welded to prevent RF inter-modulation and antenna is completely protected within a high-tech ruggedized radome to ensure survivability in the worst environments. The compact size of fiber glass collinear antenna allows easy handling and shipping.

CONSTRUCTIONS: The MC6-160 is a center fed design which eliminates the distortion of the radiation pattern and ensures a true omni-directional horizontal pattern. The special stub matching is used for smooth VSWR and constant gain over the specified frequency band. The collinear antenna consist of large diameter brass radiating elements stacked vertically, fed in phase and enclosed in fiberglass tube. The antenna termination is enclosed at bottom of the antenna for complete weather protection. The stainless steel mounting hardware is supplied with the antenna.



ELECTRICAL SPECIFICATIONS:

Frequency Range	156 - 162 MHz
Gain	6 dBi.
Bandwidth	Entire Band
Polarization	Vertical
Input Impedance	50 Ohms
Radiation Pattern	Omni Directional
Vertical Beam-width – Half Power Points	36 Degrees
VSWR	1.5 : 1
RF Power Handling Capacity	250 Watts
Input Termination	N-Female

MECHANICAL SPECIFICATIONS:

Mounting Hardware	Stainless Steel
Gross Weight	5 Kgs.
Wind Rating	200 Km/Hr.
Overall Length	2.9 Meters
Shipping Length	3.0 Meters
Support Pipe Outer Diameter	51 mm
Support Pipe Material	Aluminum
Maximum Mount Pipe Diameter	51 mm (2 Inches)
Enclosure Materials	Fiberglass
Enclosure Outer Diameter	44 mm
Enclosure Length	2450 mm
Radiating Elements - Materials	Brass

ENVIRONMENTAL SPECIFICATIONS:

Operating Temperature	(-) 30 to +70 Degrees Celsius
Storage Temperature	(-) 40 to +80 Degrees Celsius
Humidity	0 to 95% RH

Note: All information contained in the datasheet is subject to change without any prior notice.